




# SYMMONS® ShowerOff®



3-330

Exposed Shower System

## Specification Submittal

<b>Model Numbers</b>	<b>Feature Highlights</b>
<input type="checkbox"/> <b>3-330</b> <i>ShowerOff® Exposed Shower System</i>	<ul style="list-style-type: none"> <li>Exposed shower limiter valve with integral stop</li> <li>Union and street ell with escutcheon</li> <li>20" head riser with extended head bracket</li> <li>Fre-Flo shower head with adjustable spray</li> <li>Standard 1.5 gpm (5.7L/min) aerator</li> <li>Standard 2.0 gpm (7.6L/min) aerator</li> </ul>
<b>Options/ Modifications</b>	<b>Warranty</b>
<input type="checkbox"/> <b>-A</b> <i>Anchor plate for use with ceramic tile</i> <input type="checkbox"/> <b>-B</b> <i>Back plate and bolts</i> <input type="checkbox"/> <b>-1.5</b> <i>1.5 gpm (5.7 L/min) aerator</i> <input type="checkbox"/> <b>-2.0</b> <i>2.0 gpm (7.6 L/min) aerator</i> <b>Note:</b> Append appropriate -suffix to model number.	<p><b>Limited Lifetime</b> - to the original end purchaser in consumer/residential installations.</p> <p><b>10 Years</b> - for commercial/industrial installations. Refer to <a href="http://www.symmons.com/warranty">www.symmons.com/warranty</a> for complete warranty information.</p> 
<b>Compliance</b> - A112.18.1/CSA B125.1 	

## Architectural/ Engineering Specification

Symmons ShowerOff Exposed Shower System \_\_\_\_\_ with exposed shower limiter valve with integral stop, wall flange, union and street ell with escutcheon. 20" head riser with extended head bracket. Fre-Flo shower head with adjustable spray. Nozzle-type design for maximum protection against hard water mineral build-up. 10 Year Commercial Warranty. ANSI A112.18.1 certified. Available options: "A - Anchor plate for use with ceramic tile", "B - Back plate and bolts", "1.5 - 1.5 gpm (5.7 L/min) aerator", "2.0 - 2.0 gpm (7.6L/min) aerator".

# Dimensions

