

Location:




SYMMONS® Oxford™

Tub and Shower System 4202

Specification Submittal



Feature Highlights

- Symmons tub and shower system with lever handle
- Symmons Temptrol® pressure balancing mixing valve with adjustable stop screw to limit handle turn
- Showerhead #422SH and mounting bracket
- Standard flow rate is 2.5 gpm (9.5 L/min) 
- Diverter tub spout
- Polished chrome finish

Model Numbers

- ☐ 4202Tub & Shower System with Symmons Temptrol® mixing valve p/n 4000-BODY
- ☐ 4202-TRMTrim only, valve must be ordered separately
- ☐ 4000-BODY.....Symmons Temptrol® mixing valve without trim
- ☐ 4000-X-BODY....Symmons Temptrol® mixing valve without trim. Valve includes integral service stops to allow water shut-off for service.



Finish Options / Modifications

Append appropriate -suffix to model number.

- ☐ -STN Satin nickel
- ☐ -ORB Oil Rubbed Bronze
- Polished chrome (standard finish)

Options / Modifications

Append appropriate -suffix to model number.

- ☐ -IPS 1/2 inch female IPS connections on Symmons Temptrol® mixing valve
- ☐ -X Symmons Temptrol® pressure balancing mixing valve includes integral service stops to allow water shut-off for service, p/n 4000-X-BODY. (Option only applies when ordering model 4202.)
- ☐ -L/HD Showerhead is not included Includes showerhead arm and flange only .
- ☐ -VP Vandal resistant
- ☐  -2.0 2.0 (7.6 L/min) Flow rate restrictor
- ☐  -1.5 1.5 (5.7 L/min) Flow rate restrictor

Standards / Certifications

ASME A112.18.1-2005/CSA B125.1-05

Warranty

- Limited Lifetime - to the original end purchaser in consumer installations.
- 5 years - for commercial installations

Dimensions Oxford Tub-Shower System, 4202

