



Location:



4306-TRM, 4306TRMTC
Tub/Shower/Hand Shower Trim
Specification Submittal



Model Numbers		Feature Highlights	
<input type="checkbox"/> 4306-TRM	Tub/Shower/Hand Shower Trim, Temptrol Pressure Balancing Tub/Shower Valve and Symmons Triple Outlet Diverter valve ordered separately	<ul style="list-style-type: none">Sereno Tub/Shower/Hand Shower TrimRequires Temptrol® Pressure Balancing Tub/Shower ValveRequires Symmons Triple Outlet Diverter ValveMetal lever handlesCradle for hand shower wand8" non-diverter tub spoutDual checks for backflow protection60" flexible metal hose1 mode hand shower wand1 mode showerhead2.0 gpm (7.6 L/min) flow restrictorsComponents shall be metal and nonmetallic construction, plated in standard Polished Chrome finishAvailable with TA-10 flow control spindle and T-12A cap assembly for Temptrol valve bodies installed with Test Cap (order p/n 4306TRMTC)For optional in-line vacuum breaker order p/n EF-109	
<input type="checkbox"/> 4306TRMTC	Tub/Shower/Hand Shower Trim with TA-10 flow control spindle and T-12A cap assembly, must order Temptrol valve with Test Cap		
Options/ Modifications		Warranty	
<input type="checkbox"/> 1.5	1.5 gpm (5.7 L/min) flow restrictor	Limited Lifetime - to the original end purchaser in consumer/residential installations. 10 Years - for commercial/industrial installations. Refer to www.symmons.com/warranty for complete warranty information.	
<input type="checkbox"/> L1	Less showerhead		
<input type="checkbox"/> L2	Less hand shower wand		
<input type="checkbox"/> L6	Less tub spout		
<input type="checkbox"/> STN	Satin Nickel finish		
Note: Append appropriate -suffix to model number.			
Compliance			
- ASME A112.18.1/CSA B125.1			
			


Architectural/ Engineering Specification

Symmons Sereno Tub and Shower and Hand Shower Trim _____ Includes Sereno Tub and Shower and Hand Shower Trim, Requires Temptrol® Pressure Balancing Tub and Shower Valve, Requires Symmons Triple Outlet Diverter Valve, Metal lever handles, Cradle for hand shower wand, 8" non-diverter tub spout, Dual checks for backflow protection, 60" flexible metal hose, 1 mode hand shower wand, 1 mode showerhead, 2.0 gpm (7.6 L/min) flow restrictors, Components shall be metal and nonmetallic construction, plated in standard Polished Chrome finish, Available with TA-10 flow control spindle and T-12A cap assembly for Temptrol valve bodies installed with Test Cap (order p/n 4306TRMTC), For optional in-line vacuum breaker order p/n EF-109. 10 Year Commercial Warranty. ASME A112.18.1/ CSA B125.1 compliant. Available options: "1.5 - 1.5 gpm (5.7 L/min) flow restrictor", "L1 - Less showerhead", "L2 - Less hand shower wand", "L6 - Less tub spout", "STN - Satin Nickel finish".



4306-TRM, 4306TRMTC

Dimensions



Notes:

- 1) Valve body and piping not included and shown as reference only.
- 2) Plaster shield (p/n T-176) for dry wall, plaster or other type walls 1/2" or greater.
- 3) All dimensions measured from nominal rough-in.
- 4) Dimensions subject to change without notice.