




1-210
Tub/Shower System
Specification Submittal

Location:



Model Numbers

☐ **1-210** Safetymix Tub/Shower System

Options/Modifications

- ☐ **TRM** **Trim only, valve body ordered separately**
- ☐ **X** **Integral service stops—allows water shut-off at valve for service**

Note: Append appropriate -suffix to model number.

Compliance

- ASME A112.18.1/CSA B125.1




Feature Highlights

- Safetymix Pressure-Balancing mixing valve with lever handle
- Adjustable stop screw to limit handle turn
- Push-button diverter with volume control for shower head
- Super shower head with arm and flange
- Tub spout
- Standard flow rate 2.0 gpm (7.6 L/min)

Warranty

Limited Lifetime - for residential installations.
10 Years - for commercial/industrial installations.
Refer to www.symmons.com/warranty for complete warranty information.



Architectural/Engineering Specification

Symmons Safetymix Tub and Shower System _____ Includes Safetymix Pressure-Balancing mixing valve with lever handle, Adjustable stop screw to limit handle turn, Push-button diverter with volume control for shower head, Super shower head with arm and flange, Tub spout, Standard flow rate 2.0 gpm (7.6 L/min). 10 Year Commercial Warranty. ASME A112.18.1/CSA B125.1 compliant. Available options: "TRM - Trim only, valve body ordered separately", "X - Integral service stops—allows water shut-off at valve for service".



Dimensions

