



## S5598TRM Shower/Hand Shower Trim Specification Submittal

Location:

### Model Numbers

- ☐ **S5598TRM**  
Shower/Hand Shower Trim
- Valve Options:**  
-S262 Series Temptrol® VersaFlex™ Shower Valve with TRM modifier  
-S162 Series Temptrol VersaFlex Shower Valve requires TC modifier

### Feature Highlights

- Elm Shower/Hand Shower Trim.
- Requires Temptrol VersaFlex Pressure-Balancing Shower Valve.
- Integral diverter.
- Metal lever handle.
- Dual checks for backflow protection.
- 60" flexible metal hose.
- 7-mode HydroMersion™ hand shower wand with Non-Positive Shutoff (NPSO).
- 7-mode Hydromersion showerhead with Non-Positive Shutoff (NPSO).
- Standard 2.0 gpm (7.6 L/min) flow restrictor.
- Components shall be metal and nonmetal construction, plated in standard Polished Chrome finish.

### Compliance

- ASME® A112.18.1/CSA® B125.1
- WaterSense® 1.5 gpm (5.7 L/min) 2.0 gpm (7.6 L/min)
- Lever handle and hand shower wand meet ADA requirements for operation



### Options/Modifications

- ☐ **15** 1.5 gpm (5.7 L/min) flow restrictor
- ☐ **BBZ** Brushed Bronze finish
- ☐ **MB** Matte Black finish
- ☐ **STN** Satin Nickel finish
- ☐ **L1** Less showerhead
- ☐ **L2** Less hand shower wand
- ☐ **L3** Less showerhead and hand shower (head and wand only)
- ☐ **L4** Less head, arm, and flange
- ☐ **L5** Less hand shower system
- ☐ **L7** Less handle
- ☐ **TC** Test Cap Trim (includes TA-10™ & T-12A) used with S162 Series Temptrol VersaFlex Valve

### Warranty

**Limited Lifetime** - for residential installations.  
**10 Years** - for commercial/industrial installations.  
Refer to [www.symmons.com/warranty](http://www.symmons.com/warranty) for complete warranty information.



### SKU Builder

Series	Finish	Modifier	Flow Rate	Trim (required)	Test Cap	Final SKU
S5598	STN		1.5	TRM		S5598STN15TRM
S5598	MB	L3		TRM	TC	S5598MBL3TRMTC

**Notes:** No more than two modifiers (L1-L7) permitted when ordering. Modifiers will list in numerical order.

### Architectural/Engineering Specification

Symmons Elm Shower and Hand Shower Trim \_\_\_\_\_ Includes Elm Shower/Hand Shower Trim for Temptrol VersaFlex Pressure-Balancing Shower Valve. Features integral diverter, metal lever handle, dual checks for backflow protection, 60" flexible metal hose, 7-mode HydroMersion hand shower wand with NPSO, 7-mode HydroMersion showerhead with NPSO, and standard 2.0 gpm (7.6 L/min) flow restrictors. Components shall be metal and nonmetal construction, plated in standard Polished Chrome finish. 10-Year Commercial Warranty. ASME A112.18.1/CSA B125.1, WaterSense 1.5 gpm (5.7 L/min) and 2.0 gpm (7.6 L/min) compliant. Lever handle and hand shower wand meet ADA requirements for operation. Available options: 15 = 1.5 gpm (5.7 L/min) flow restrictor, L1 = Less showerhead, L2 = Less hand shower wand, L3 = Less showerhead and hand shower (head and wand only), L4 = Less head, arm, and flange, L5 = Less hand shower system, L7 = Less handle, BBZ = Brushed Bronze finish, MB - Matte Black finish, STN = Satin Nickel finish, and TC = Test Cap Trim.

## Dimensions

