



Location:



5305-TRM, 5305TRMTC Shower/Hand Shower Trim Specification Submittal



Feature Highlights	Options/Modifications
<ul style="list-style-type: none">• Museo Shower/Hand Shower Trim• Requires Temptrol® Pressure Balancing Shower Valve• Requires Symmons Dual Outlet Diverter Valve• Metal lever handles• Cradle for hand shower wand• Dual checks for backflow protection• 60" flexible metal hose• 2 mode hand shower wand• 1 mode showerhead• 2.0 gpm (7.6 L/min) flow restrictors• Tub spout not included• Components shall be metal and nonmetallic construction, plated in standard Polished Chrome finish• Available with TA-10 flow control spindle and T-12A cap assembly for Temptrol valve bodies installed with Test Cap (order p/n 5305TRMTC)• For optional in-line vacuum breaker order p/n EF-109	<div><input type="checkbox"/> -1.5  1.5 gpm (5.7 L/min) flow restrictor</div> <div><input type="checkbox"/> -L1 Less showerhead</div> <div><input type="checkbox"/> -L2 Less hand shower wand</div> <div><input type="checkbox"/> -L3 Less showerhead & hand shower wand</div> <div><input type="checkbox"/> -BLK Polished Graphite</div> <div>Note: Append appropriate -suffix to model number.</div>
Model Numbers	Warranty
<div><input type="checkbox"/> 5305-TRM Shower/Hand Shower Trim, Temptrol Pressure Balancing Shower Valve and Symmons Dual Outlet Diverter valve ordered separately</div> <div><input type="checkbox"/> 5305TRMTC Shower/Hand Shower Trim with TA-10 flow control spindle and T-12A cap assembly, must order Temptrol valve with Test Cap</div>	<div>Limited Lifetime - to the original end purchaser in consumer/residential installations.</div> <div>10 Years - for commercial/industrial installations. Refer to www.symmons.com/warranty for complete warranty information.</div> <div></div>

Architectural/ Engineering Specification

Symmons _____ With Museo Shower/Hand Shower Trim, requires Temptrol® pressure balancing shower valve, Requires Symmons Dual Outlet Diverter Valve, metal lever handles, Cradle for hand shower wand, Dual checks for backflow protection, 60" flexible metal hose, 2 mode hand shower wand, 1 mode showerhead, 2.0 gpm (7.6 L/min) flow restrictor, Tub spout not included, components shall be metal and nonmetallic construction, plated in standard Polished Chrome finish, available with TA-10 flow control spindle and T-12A cap assembly for Temptrol valve bodies installed with Test Cap (order p/n 5401TRMTC), For optional in-line vacuum breaker order p/n EF-109. 10 Year commercial Warranty. ASME A112.18.1/CSA B125.1, Complaint. Available options include "1.5 - 1.5 gpm (5.7 L/min) flow restrictor", "L1 - Less showerhead", "L2 - Less hand shower wand", "L3 - Less showerhead & hand shower wand", "BLK - Polished Graphite".

