






1-1170VT-H401-V                      Location:  
**Visu-Temp® Shower/Hand Shower System**  
**Specification Submittal**



Model Numbers	Feature Highlights
<input type="checkbox"/> <b>1-1170VT-H401-V</b> Visu-Temp® Shower/Hand Shower System	<ul style="list-style-type: none"><li>▪ Symmons Visu-Temp® pressure-balancing mixing valve with Clear-vue™ thermometer and adjustable stop screw to limit handle turn, #4-5000VT.</li><li>▪ Euro-flo single mode wall/hand shower with flexible metal hose, wall connection, flange and cradle for mounting hand shower, #H401-V that includes wand #EF-118.</li><li>▪ Lever diverter, 2DIV-BODY with volume control for showerhead and hand shower.</li><li>▪ Euro-flo single mode self-cleaning showerhead #4-241.</li><li>▪ Showerhead mounting arm and flange, # 300.</li><li>▪ Standard flow rate is 2.0 gpm (7.6 L/min) Optional aerator available in lower flow rates.</li><li>▪ Polished Chrome finish (standard).</li><li>▪ For optional in-line vacuum breaker order p/n EF-109.</li></ul>
Options/ Modifications	Warranty
<input type="checkbox"/> -TRM              Trim only, valve body ordered separately	<b>Limited Lifetime</b> - for residential installations.
<input type="checkbox"/> -X                  Symmons Temptrol® pressure balancing mixing valve includes integral service stops to allow water shut-off for service	<b>10 Years</b> - for commercial/industrial installations.
<input type="checkbox"/> -X-CHKS          Integral check stops: Used where a positive shut-off device is used down stream of mixing valve	Refer to <a href="http://www.symmons.com/warranty">www.symmons.com/warranty</a> for complete warranty information.
<input type="checkbox"/> -X-3/4              3/4 inch valve to increase water flow approximately 20%	
<input type="checkbox"/> -72                  Includes 72" hose	
<input type="checkbox"/> -NS                  Non-shared diverter valve	
<input type="checkbox"/> -1.5                  1.5 gpm (5.7 L/min) flow rate restrictor	
<input type="checkbox"/> L1                   Less showerhead	
<input type="checkbox"/> L2                   Less hand shower	
<input type="checkbox"/> L3                   Less showerhead and hand shower	
<input type="checkbox"/> L4                   Less showerhead, arm, and flange	
<input type="checkbox"/> L5                   Less hand shower system	
<b>Note:</b> -Append appropriate -suffix to model number. -When ordering L1-L7 modifiers, remove hyphens from model number.	
Compliance	
- ASME A112.18.1/CSA B125.1.	
	

## Architectural/Engineering Specification

Symmons Visu-Temp Shower and Hand Shower System \_\_\_\_\_ Includes Visu-Temp Pressure-Balancing mixing valve with Clear-Vue™ thermometer, adjustable stop screw to limit handle turn, lever diverter with volume control for shower head and hand shower, single mode showerhead with arm and flange, single mode wall/hand shower with flexible 5' metal hose, dual checks for backflow protection, wall connection and flange, cradle for hand shower mounting. Standard flow rate 2.0 gpm (7.6 L/min). Polished Chrome finish (standard). 10-Year Commercial Warranty. ASME A112.18.1/CSA B125.1 compliant. Available options: 1.5 = 1.5 gpm (5.7 L/min) flow restrictor, X = Integral service stops—allows water shut-off at valve for service, X-3/4 = 3/4" valve to increase flow approximately 20%, X-CHKS = Integral check stops—for use in installations where a positive shut-off device is used downstream of mixing valve, NS = Non-shared diverter valve, TRM = Trim only, L1 = Less handle, L2 = Less hand shower, L3 = Less showerhead and hand shower, L4 = Less showerhead, arm, & flange, L5 = Less hand shower system.

## Dimensions

### Dimensions Visu-Temp Shower System with Hand Shower, 1-1170VT-H401-V

