## Location:



SLC-5512 Lavatory Faucet **Specifications Submittal** 



Model Numbers	Feature Highlights
□ SLC-5512-1.0 Centerset Lavatory Faucet with pop-up drain assembly with lift rod	<ul> <li>4 inch centerset lavatory faucet with lever handles</li> <li>Commercial grade 1/4 turn ceramic disc valve cartridge for drip free performance</li> <li>Standard flow rate is 1.0 gpm (3.8 L/min)         Optional lower flow rate restrictor available     </li> <li>Polished chrome finish (standard)</li> </ul>
Options / Modifications	
Append appropriate -suffix to model number  Graph -0.5-NA 0.5 gpm (1.9 L/min) flow rate restrictor	Standards / Certifications
	<ul> <li>ASME A112.18.1/ CSA B125.1</li> <li>Low lead compliant, AB1953/S.152/S.3874</li> <li>WaterSense 1.0gpm(3.8L/min)</li> <li>Americans with Disabilities Act (ADA) compliant</li> </ul>
Finish Options / Modifications	Warranty
Append appropriate -suffix to model number  -STN Satin Nickel -SBZ Seasoned Bronze - Polished Chrome (standard finish) -MB Matte Black finish -BBZ Brushed Bronze finish	Limited Lifetime - to the original end purchaser in consumer/residential installations.  10 Years - for commercial/industrial installations. Refer to www.symmons.com/warranty for complete warranty information.
Architectural/ Engineering Specification	1

Symmons Elm \_\_\_\_\_ With 4 inch centerset lavatory faucet with lever handles, Commercial grade 1/4 turn ceramic disc valve cartridge for drip free performance, Standard flow rate is 1.0 gpm (3.8 L/min) Optional lower flow rate restrictor available, Polished chrome finish, 0.5 gpm (1.9 L/min) flow rate restrictor, Add red and blue indicators to the handle. 10 Year Commercial Warranty. ASME A112.18.1/ CSA B125.1, AB1953/S.152/S.3874,

WaterSense® Certified (1.0 gpm & 1.5 gpm), complaint. Available options include: "-0.5-NA - 0.5 gpm (1.9 L/min) flow rate restrictor", "-STN - Satin nickel", "-SBZ - Seasoned Bronze", "-MB - Matte Black finish", "-BBZ - Brushed Bronze finish".



SLC-5512

## **Dimensions**

