



S6792TRM
Tub/Shower Trim

Location:

Specification Submittal

Model Numbers

- S6792TRM**
Tub/Shower Trim

Valve Options:

- S262 Series Temptrol® VersaFlex™ Shower Valve with TRM modifier.
- S162 Series Temptrol VersaFlex Shower Valve requires TC modifier.

Feature Highlights

- Identity Tub/Shower Trim.
- Requires Temptrol VersaFlex Pressure-Balancing Shower Valve.
- Integral diverter control.
- Metal lever handle.
- 5-1/8" slip-on tub spout.
- Single-mode HydroMersion™ showerhead.
- Standard 2.0 gpm (7.6 L/min) flow restrictor.
- Components shall be metal and nonmetal construction, plated in standard Polished Chrome finish.

Compliance

- ASME® A112.18.1/CSA® B125.1
- WaterSense® 1.5 gpm (5.7 L/min)
2.0 gpm (7.6 L/min)
- Lever handle meets ADA requirements for operation.



Options/Modifications

- 15**  1.5 gpm (5.7 L/min) flow restrictor
- L1** Less showerhead
- L4** Less head, arm, and flange
- L7** Less handle
- TC** Test Cap Trim (includes TA-10™ & T-12A) used with S162 Series Temptrol VersaFlex Shower Valve
- BBZ** Brushed Bronze finish
- MB** Matte Black finish
- STN** Satin Nickel finish

Warranty

Limited Lifetime - for residential installations.
10 Years - for commercial/industrial installations.
Refer to www.symmons.com/warranty for complete warranty information.



SKU Builder

Series	Finish	Modifier	Flow Rate	TRM (required)	TC	Final SKU
S6792	STN		15	TRM		S6792STN15TRM
S6792	MB	L2		TRM	TC	S6792MBL2TRMTC

Notes: No more than two modifiers (L1-L7) permitted when ordering. Modifiers will list in numerical order.

Architectural/Engineering Specification

Symmons Identity Tub and Shower Trim _____ Includes Identity Tub/Shower Trim for Temptrol VersaFlex Pressure-Balancing Shower Valve. Features integral diverter control, metal level handle, 5-1/8" slip-on tub spout, single-mode HydroMersion™ showerhead, and standard 2.0 gpm (7.6 L/min) flow restrictor. Components shall be metal and nonmetal construction, plated in standard Polished Chrome finish. 10-Year Commercial Warranty. ASME A112.18.1/CSA B125.1, WaterSense 1.5 gpm and 2.0 gpm compliant. Lever handle meets ADA requirements for operation. Available options include: 15 = 1.5 gpm (5.7 L/min) flow restrictor, L1 = Less showerhead, L7 = Less handle, TC = Test Cap Trim, BBZ = Brushed Bronze finish, MB = Matte Black finish, and STN = Satin Nickel finish.

