




Location:



4-226F
Clear-Flo Shower Heads
Specification Submittal



Model Numbers		Feature Highlights	
<input type="checkbox"/> 4-226F	Clear-Flo Shower Heads	<ul style="list-style-type: none">adjustable spraystandard ball joint connection	
Options/ Modifications			
<input type="checkbox"/> M	Male thread connection (1/2” MIPS)		
<input type="checkbox"/> VP	Vandal resistant		
<input type="checkbox"/> 1.5	1.5 gpm (5.7 L/min) flow restrictor		
<input type="checkbox"/> 1.75	1.75 gpm (6.6 L/min) flow rate restrictor	Warranty	<p>Limited Lifetime - to the original end purchaser in consumer/residential installations.</p> <p>10 Years - for commercial/industrial installations. Refer to www.symmons.com/warranty for complete warranty information.</p>
<input type="checkbox"/> STN	Satin Nickel finish		
Note: Append appropriate -suffix to model number.			
Compliance			
<ul style="list-style-type: none">- ASME A112.18.1/CSA B125.1- WaterSense 1.5 gpm & 2.0 gpm		 	

Architectural/ Engineering Specification

Symmons Clear-Flo 2000 shower head _____ Includes Symmons Clear-Flo 2000 shower head with adjustable spray and standard ball joint connection. 10 Year Commercial Warranty. ASME A112.18.1/CSA B125.1 compliant. Available options: "M - Male thread connection (1/2" MIPS)", "VP - Vandal resistant", "1.5 - 1.5 gpm (5.7 L/min) flow restrictor", "1.75 - 1.75 gpm (6.6 L/min) flow rate restrictor", "STN - Satin Nickel finish".