



5596TRM
Tub/Hand Shower/Shower Trim
Specification Submittal

Location:

<p>Model Numbers</p> <p><input type="checkbox"/> 5596TRM Tub/Hand Shower/Shower Trim</p> <p>Valve Options -261 Series Temptrol® Shower Valve with TRM modifier -161 Series Temptrol Shower Valve requires TC modifiers -3DIVBODYSRT</p>	<p>Modifications</p> <ul style="list-style-type: none"> <input type="checkbox"/> 15  1.5 gpm (5.7 L/min) flow restrictor <input type="checkbox"/> TC Test Cap Trim (includes TA-10™ & T-12A) used with 161 Series Temptrol Valve. <input type="checkbox"/> L1 Less showerhead <input type="checkbox"/> L2 Less hand shower (wand only) <input type="checkbox"/> L3 Less showerhead and hand shower (head and wand only) <input type="checkbox"/> L4 Less showerhead, shower arm, and flange <input type="checkbox"/> L5 Less hand shower system (less bar/cradle, hose, wand, and elbow. <input type="checkbox"/> L7 Less handle <input type="checkbox"/> BBZ Brushed Bronze finish <input type="checkbox"/> MB Matte Black finish <input type="checkbox"/> STN Satin Nickel finish
<p>Feature Highlights</p> <ul style="list-style-type: none"> • Elm Tub/Shower/Hand Shower Trim. • Requires Temptrol Pressure-Balancing Shower Valve. • Separate three-function diverter body. • 5-7/8" Slip-on tub spout. • 60" flexible metal hose. • 7-mode HydroMersion™ hand shower with Non-Positive Shutoff (NPSO). • 7-mode HydroMersion showerhead with Non-Positive Shutoff (NPSO). • Standard 2.0 gpm (7.6 L/min) flow restrictors. • Components made from metal and nonmetal materials plated in standard Polished Chrome finish. 	<p>Compliance</p> <ul style="list-style-type: none"> • ASME A112.18.1/CSA B125.1 • WaterSense 1.5 gpm (5.7 L/min) 2.0 gpm (7.6 L/min) • Lever handle and hand shower wand meet ADA requirements for operation <div style="text-align: right;">    </div>
<p>Warranty</p> <p>Limited Lifetime - for residential installations. 10 Years - for commercial/industrial installations. Refer to www.symmons.com/warranty for complete warranty information.</p> 	

SKU Builder

Series	Finish	Modifier	Flow Rate	Trim (required)	Test Cap	Final SKU
5596	STN		15	TRM		5596STN15TRM
5596	MB	L3		TRM	TC	5596MBL3TRMTC

Notes: No more than two modifiers (L1-L7) permitted when ordering. Modifiers will list in numerical order.

Architectural/Engineering Specification

Symmons Elm Tub and Shower and Hand Shower System _____ Includes Elm Tub/Shower/Hand Shower Trim for the Temptrol® Pressure-Balancing Shower Valve. Features 5-7/8" Slip-on tub spout, 60" flexible metal hose, 7-mode HydroMersion hand shower with NPSO, 7-mode HydroMersion showerhead with NPSO, and standard 2.0 gpm (7.6 L/min) flow restrictors. Components made from metal and nonmetal materials, plated in standard Polished Chrome finish. 10-Year Commercial Warranty. Lever handle and hand shower wand meet ADA requirements for operation. ASME A112.18.1/CSA B125.1, WaterSense 1.5 gpm (5.7 L/min) and 2.0 gpm (7.6 L/min) compliant. Available options: 15 = 1.5 gpm (5.7 L/min) flow restrictor, L1 - Less showerhead, L2 = Less hand shower (wand only), L3 = Less showerhead and hand shower (head and wand only), L4 = Less shower arm and flange, L5 = Less hand shower system, L7 = Less handle, BBZ = Brushed Bronze finish, MB = Matte Black finish, STN = Satin Nickel finish, and TC = Test Cap Trim.

