

Location:



5506-TRM, 5506TRMTC, 5506TRM Tub/Shower/Hand Shower Trim Specification Submittal



Feature Highlights	Options/Modifications
<ul style="list-style-type: none"> • Elm Tub/Shower/Hand Shower Trim • Requires Temptrol® Pressure Balancing Tub/Shower Valve • Requires Symmons Triple Outlet Diverter Valve • Metal lever handles • Cradle for hand shower wand • 5-7/8" non-diverter tub spout • Dual checks for backflow protection • 60" flexible metal hose • 3 mode hand shower wand • 5 mode showerhead • 2.0 gpm (7.6 L/min) flow restrictors • Components shall be metal and nonmetallic construction, plated in standard Polished Chrome finish • Available with TA-10 flow control spindle and T-12A cap assembly for Temptrol valve bodies installed with Test Cap (order p/n 5506TRMTC) • For optional in-line vacuum breaker order p/n EF-109 	<ul style="list-style-type: none"> <input type="checkbox"/> -1.5  1.5 gpm (5.7 L/min) flow restrictor <input type="checkbox"/> L1 Less showerhead <input type="checkbox"/> L2 Less hand shower wand <input type="checkbox"/> L3 Less showerhead & hand shower wand <input type="checkbox"/> -SBZ Seasoned Bronze Finish <input type="checkbox"/> -STN Satin Nickel finish <input type="checkbox"/> -MB Matte Black Finish <input type="checkbox"/> -BBZ Brush Bronze Finish <p>Note: Append appropriate -suffix to model number.</p>
Model Numbers	Warranty
<ul style="list-style-type: none"> <input type="checkbox"/> 5506-TRM Tub/Shower/Hand Shower Trim, Temptrol Pressure Balancing Tub/Shower Valve and Symmons Triple Outlet Diverter valve ordered separately <input type="checkbox"/> 5506TRMTC Tub/Shower/Hand Shower Trim with TA-10 flow control spindle and T-12A cap assembly, must order Temptrol valve with Test Cap <input type="checkbox"/> 5506TRM Tub/Shower/Hand Shower Trim, Temptrol Pressure Balancing Tub/Shower Valve and Symmons Triple Outlet Diverter valve ordered separately <p>Note: -Append appropriate -suffix to model number. -When ordering L1-L7 modifiers, remove hyphens from model number.</p>	<p>Limited Lifetime - to the original end purchaser in consumer/residential installations. 10 Years - for commercial/industrial installations. Refer to www.symmons.com/warranty for complete warranty information.</p> 
Compliance	
<ul style="list-style-type: none"> • ASME A112.18.1/CSA B125.1 	

Architectural/ Engineering Specification

Symmons Tub and Shower and Hand Shower Trim _____ With Elm Tub and Shower and Hand Shower Trim, requires Temptrol® pressure balancing Tub/shower valve, Requires Symmons Triple Outlet Diverter Valve, metal lever handle, Cradle for hand shower wand, 5-7/8" non-diverter tub spout, Dual checks for backflow protection, 60" flexible metal hose, 3 mode hand shower wand, 5 mode showerhead, 2.0 gpm (7.6 L/min) flow restrictor, Tub spout not included, components shall be metal and nonmetallic construction, plated in standard Polished Chrome finish, available with TA-10 flow control spindle and T-12A cap assembly for Temptrol valve bodies installed with Test Cap (order p/n 5506TRMTC), For optional in-line vacuum breaker order p/n EF-109. 10 Year commercial Warranty. ASME A112.18.1/CSA B125.1, Complaint. Available options include "-1.5 - 1.5 gpm (5.7 L/min) flow restrictor", "L1 - Less showerhead", "L2 - Less hand shower wand", "L3 - Less showerhead & hand shower wand", "-SBZ - Seasoned Bronze Finish", "-STN - Satin nickel finish", "-MB - Matte Black Finish", "-BBZ - Brush Bronze Finish".

Dimensions
