



SYMMONS® Visu-Temp®




1-250VT-H401-V

Location:

1 Hand Shower System

Specification Submittal



Model Numbers	Feature Highlights
<input type="checkbox"/> 1-250VT-401-V Shower and Hand Shower System with Symmons Visu-Temp® pressure balancing mixing valve	<ul style="list-style-type: none">• Visu-Temp Pressure Balancing valve.• Adjustable stop screw to limit handle turn.• Metal lever handle.• 1 mode hand shower wand.• Cradle for hand shower.• 60" flexible metal hose.• Standard 2.0 gpm (7.6 L/min) flow restrictor.• Shall be metal and nonmetallic construction.• Plated in standard Polished Chrome finish.
Options/Modifications	Warranty
<input type="checkbox"/> -1.5  1.5 gpm (5.7 L/min) flow restrictor	Limited Lifetime - for residential installations. 10 Years - for commercial/industrial installations. Refer to www.symmons.com/warranty for complete warranty information.
<input type="checkbox"/> -TRM Trim only	
<input type="checkbox"/> -X Integral service stops - allows water shutoff at valve for service	Compliance
<input type="checkbox"/> -X-3/4 3/4" valve to increase flow approx. 20%	<ul style="list-style-type: none">• ASME A112.18.1/CSA B125.1.
<input type="checkbox"/> -X-CHKS Integral check stops - for use in installations where a positive shut-off device is used downstream of mixing valve	
Note: Append appropriate -suffix to model number.	

Architectural/Engineering Specification

Symmons Visu-Temp 1 Hand Shower System _____ Includes visu-Temp Pressure Balancing valve, adjustable stop screw to limit handle turn, metal lever handle, 1 mode hand shower wand, cradle for hand shower, 60" flexible metal hose, standard 2.0 gpm (7.6 L/min) flow restrictor, shall be metal and nonmetallic construction. Plated in standard Polished Chrome finish. 10-Year Commercial Warranty. ASME A112.18.1/CSA B125.1 compliant. Available options: 1.5 = 1.5 gpm (5.7 L/min) flow restrictor, TRM = Trim only, X = Integral service stops - allows water shutoff at valve for service, X-3/4 = 3/4" valve to increase flow approx. 20%, X-CHKS = Integral check stops - for use in installations where a positive shut-off device is used downstream of mixing valve.

Visu-Temp Hand Shower, 1-250VT-H401-V

