



S3594BTRM  
Tub/Hand Shower Trim  
**Specification Submittal**

Location:

**Model Numbers**

- S3594BTRM**  
Tub/Hand Shower Trim

**Valve options:**  
-S262 Series Temptrol® VersaFlex™ Shower Valve with TRM modifier  
-S162 Series Temptrol VersaFlex Shower Valve requires TC modifier

**Feature Highlights**

- Dia Tub/Hand Shower Trim.
- Requires Temptrol VersaFlex Pressure-Balancing Shower Valve.
- Integral diverter control.
- Metal lever handle.
- 7" tub spout.
- 30" slide bar for hand shower.
- 60" flexible metal hose.
- 7-mode HydroMersion™ hand shower with Non-Positive Shutoff (NPSO).
- Dual checks for backflow protection.
- Standard 2.0 gpm (7.6 L/min) flow restrictor.
- Components shall be metal and nonmetal construction, plated in standard Polished Chrome finish.

**Compliance**

- ASME® A112.18.1/CSA® B125.1
- WaterSense® 1.5 gpm (5.7 L/min) 1.75 gpm (6.6 L/min) 2.0 gpm (7.6 L/min)
- Lever handle meets ADA requirements for operation



**Options/ Modifications**

- 15** 1.5 gpm (5.7 L/min) flow restrictor
- 175** 1.75 gpm (6.6 L/min) flow restrictor
- Delete Suffix B** Chrome plastic escutcheon on valve with color graphic/indicators in place of standard brass escutcheon
- L2** Less hand shower
- L5** Less hand shower system (less bar/cradle, hose, wand, and elbow).
- L6** Less tub spout
- L7** Less handle
- BBZ** Brushed Bronze finish
- MB** Matte Black finish
- STN** Satin Nickel finish
- TC** Test Cap Trim (includes TA-10™ & T-12A) used with S162 Series Temptrol VersaFlex Shower Valve

**Warranty**

**Limited Lifetime** - for residential installations.  
**10 Years** - for commercial/industrial installations.  
Refer to [www.symmons.com/warranty](http://www.symmons.com/warranty) for complete warranty information.



**SKU Builder**

Series	Finish	Modifier	Flow Rate	TRM (required)	TC	Final SKU
S3594B	STN		15	TRM		S3594BSTN15TRM
S3594	MB	L1		TRM	TC	S3594BMBL1TRMTC

**Notes:** No more than two modifiers (L1-L7) permitted when ordering. Modifiers will list in numerical order.

**Architectural/ Engineering Specification**

Symmons Dia Tub and Hand Shower Trim \_\_\_\_\_ Includes Dia Tub and Hand Shower Trim for Temptrol VersaFlex Pressure-Balancing Shower Valve. Features integral diverter control, metal lever handle, 7" tub spout, 30" slide bar for hand shower, 60" flexible metal hose, 7-mode HydroMersion hand shower with NPSO, dual checks for backflow protection, and standard 2.0 gpm (7.6 L/min) flow restrictor. Components shall be metal and nonmetal construction, plated in standard Polished Chrome finish. 10-Year Commercial Warranty. ASME A112.18.1/CSA B125.1, WaterSense 1.5 gpm (5.7 L/min), 1.75 gpm (6.6 L/min), 2.0 gpm (7.6 L/min) compliant. Lever handle meets ADA requirements for operation. Available options: 15 = 1.5 gpm (5.7 L/min) flow restrictor, 175 = 1.75 gpm (6.6 L/min) flow restrictor, Delete Suffix B = Chrome plastic escutcheon, L2 = Less hand shower, L5 = Less hand shower system, L6 = Less tub spout, L7 = Less handle, TC = Test Cap Trim, BBZ = Brushed Bronze finish, MB = Matte Black finish, and STN = Satin Nickel finish.

