






1-210VT  
Tub/Shower System  
**Specification Submittal**

Location:



Model Numbers		Feature Highlights	
<input type="checkbox"/> 1-210VT	Visu-Temp Tub/Shower System	<ul style="list-style-type: none"><li>• Visu-Temp Pressure-Balancing mixing valve with integral thermometer</li><li>• Adjustable stop screw to limit handle turn</li><li>• Push-button diverter with volume control for shower head</li><li>• Super shower head with arm and flange</li><li>• Tub spout</li><li>• Standard flow rate 2.0 gpm (7.6 L/min)</li></ul>	
Options/Modifications			
<input type="checkbox"/> 1.5	1.5 gpm (5.7 L/min) flow restrictor		
<input type="checkbox"/> X	Integral service stops—allows water shut-off at valve for service		
<b>Note:</b> Append appropriate -suffix to model number.		<b>Warranty</b>	
Compliance		<b>Limited Lifetime</b> - for residential installations. <b>10 Years</b> - for commercial/industrial installations. Refer to <a href="http://www.symmons.com/warranty">www.symmons.com/warranty</a> for complete warranty information.	
- ASME A112.18.1/CSA B125.1			
			

## Architectural/Engineering Specification

Symmons Visu-Temp Tub and Shower System \_\_\_\_\_ Includes Visu-Temp Pressure-Balancing mixing valve with integral thermometer, Adjustable stop screw to limit handle turn, Push-button diverter with volume control for shower head, Super shower head with arm and flange, Tub spout, Standard flow rate 2.0 gpm (7.6 L/min). 10 Year Commercial Warranty. ASME A112.18.1/CSA B125.1 compliant. Available options: "1.5 - 1.5 gpm (5.7 L/min) flow restrictor", "X - Integral service stops—allows water shut-off at valve for service".

1-210VT

## Dimensions

