

S5594TRM
Tub/Hand Shower Trim
Specification Submittal

Location:

Model Numbers

- S5594TRM**
Tub/Hand Shower Trim
- Valve Options:**
-S262 Series Temptrol® VersaFlex™ Shower Valve with TRM modifier
-S162 Series Temptrol VersaFlex Shower Valve requires TC modifier

Feature Highlights

- Elm Tub/Hand Shower Trim.
- Requires Temptrol VersaFlex Pressure-Balancing Shower Valve.
- In-line vacuum breaker.
- 60" flexible metal hose.
- 5-7/8" tub spout.
- Single-mode HydroMersion™ hand shower wand with Non-Positive Shutoff (NPSO).
- Standard 2.0 gpm (7.6 L/min) flow restrictor.
- Components made from metal and nonmetal materials, plated in standard Polished Chrome finish.

Compliance

- ASME® A112.18.1/CSA® B125.1
- WaterSense® 1.5 gpm (5.7 L/min) and 2.0 gpm (7.6 L/min)
- Lever handle and hand shower wand meet ADA requirements for operation



Options/Modifications

- 15** 1.5 gpm (5.7 L/min) flow restrictor
- L2** Less hand shower wand
- L5** Less hand shower system (bar/cradle, hose, wand, and elbow)
- L7** Less handle
- TC** Test Cap Trim (includes TA-10™ & T-12A) *used with S162 Series Temptrol VersaFlex Shower Valve*
- BBZ** Brushed Bronze finish
- MB** Matte Black finish
- STN** Satin Nickel finish

Warranty

Limited Lifetime - for residential installations.
10 Years - for commercial/industrial installations.
Refer to www.symmons.com/warranty for complete warranty information.



SKU Builder


Series	Finish	Modifier	Flow Rate	TRM (required)	TC	Final SKU
S5594	STN		15	TRM		S5594STN15TRM
S5594	MB	L2		TRM	TC	S5594MBL2TRMTC

Notes: No more than two modifiers (L1-L7) permitted when ordering. Modifiers will list in numerical order.

Architectural/Engineering Specification

Symmons Elm Tub and Hand Shower System _____ Includes Elm Tub/Hand Shower trim for Temptrol VersaFlex Pressure-Balancing Shower Valve. Features in-line vacuum breaker, 60" flexible metal hose, 5-7/8" tub spout, 7-mode HydroMersion hand shower wand with NPSO, and standard 2.0 gpm (7.6 L/min) flow restrictor. Components made from metal and nonmetal materials, plated in standard Polished Chrome finish. 10-Year Commercial Warranty. ASME A112.18.1/CSA B125.1, WaterSense 1.5 gpm (5.7 L/min) and 2.0 gpm (7.6 L/min) compliant. Lever handle and hand shower wand meet ADA requirements for operation. Available options: 15 = 1.5 gpm (5.7 L/min) flow restrictor, L2 = Less hand shower wand, L5 = Less hand shower system (bar/cradle, hose, wand, and elbow), L7 = Less handle, TC = Test Cap Trim, BBZ = Brushed Bronze finish, MB = Matte Black finish, and STN = Satin Nickel finish.

Dimensions



Notes:

- 1) Valve body and piping not included and shown as reference only.
- 2) Plaster shield (p/n T-176) for drywall, plaster, or other type walls 1/2" or greater.
- 3) All dimensions measured from nominal rough-in.
- 4) Dimensions subject to change without notice.