

S5594TRM Tub/Hand Shower Trim Specification Submittal

Location:

Model Numbers

- ☐ **S5594TRM**
Tub/Hand Shower Trim
- Valve Options:**
 - S262 Series Temptrol® VersaFlex™ Shower Valve with TRM modifier
 - S162 Series Temptrol VersaFlex Shower Valve requires TC modifier

Feature Highlights

- Elm Tub/Hand Shower Trim.
- Requires Temptrol VersaFlex Pressure-Balancing Shower Valve.
- In-line vacuum breaker.
- 60" flexible metal hose.
- 5-7/8" tub spout.
- Single-mode HydroMersion™ hand shower wand with Non-Positive Shutoff (NPSO).
- Standard 2.0 gpm (7.6 L/min) flow restrictor.
- Components made from metal and nonmetal materials, plated in standard Polished Chrome finish.

Compliance

- ASME® A112.18.1/CSA® B125.1
- WaterSense® 1.5 gpm (5.7 L/min) and 2.0 gpm (7.6 L/min)
- Lever handle and hand shower wand meet ADA requirements for operation




Options/Modifications

- ☐ **15** 1.5 gpm (5.7 L/min) flow restrictor
- ☐ **L2** Less hand shower wand
- ☐ **L5** Less hand shower system (bar/cradle, hose, wand, and elbow)
- ☐ **L7** Less handle
- ☐ **TC** Test Cap Trim (includes TA-10™ & T-12A) *used with S162 Series Temptrol VersaFlex Shower Valve*
- ☐ **BBZ** Brushed Bronze finish
- ☐ **MB** Matte Black finish
- ☐ **STN** Satin Nickel finish

Warranty

Limited Lifetime - for residential installations.
10 Years - for commercial/industrial installations.
Refer to www.symmons.com/warranty for complete warranty information.



SKU Builder

Series	Finish	Modifier	Flow Rate	TRM (required)	TC	Final SKU
S5594	STN		15	TRM		S5594STN15TRM
S5594	MB	L2		TRM	TC	S5594MBL2TRMTC

Notes: No more than two modifiers (L1-L7) permitted when ordering. Modifiers will list in numerical order.

Architectural/Engineering Specification

Symmons Elm Tub and Hand Shower System _____ Includes Elm Tub/Hand Shower trim for Temptrol VersaFlex Pressure-Balancing Shower Valve. Features in-line vacuum breaker, 60" flexible metal hose, 5-7/8" tub spout, 7-mode HydroMersion hand shower wand with NPSO, and standard 2.0 gpm (7.6 L/min) flow restrictor. Components made from metal and nonmetal materials, plated in standard Polished Chrome finish. 10-Year Commercial Warranty. ASME A112.18.1/CSA B125.1, WaterSense 1.5 gpm (5.7 L/min) and 2.0 gpm (7.6 L/min) compliant. Lever handle and hand shower wand meet ADA requirements for operation. Available options: 15 = 1.5 gpm (5.7 L/min) flow restrictor, L2 = Less hand shower wand, L5 = Less hand shower system (bar/cradle, hose, wand, and elbow), L7 = Less handle, TC = Test Cap Trim, BBZ = Brushed Bronze finish, MB = Matte Black finish, and STN = Satin Nickel finish.

Dimensions

