

# Location



## 5505-TRM, 5505TRMTC, 5505TRM Shower/Hand Shower Trim Specification Submittal

### Feature Highlights

- Elm Shower/Hand Shower Trim
- Requires Temptrol® Pressure Balancing Shower Valve
- Requires Symmons Dual Outlet Diverter Valve
- Metal lever handles
- Cradle for hand shower wand
- Dual checks for backflow protection
- 60" flexible metal hose
- 3 mode hand shower wand
- 5 mode showerhead
- 2.0 gpm (7.6 L/min) flow restrictors
- Tub spout not included
- Components shall be metal and nonmetallic construction, plated in standard Polished Chrome finish
- Available with TA-10 flow control spindle and T-12A cap assembly for Temptrol valve bodies installed with Test Cap (order p/n 5505TRMTC)
- For optional in-line vacuum breaker order p/n EF-109

### Options/Modifications

- 1.5**  1.5 gpm (5.7 L/min) flow restrictor
- L1** Less showerhead
- L2** Less hand shower wand
- L3** Less showerhead & hand shower wand
- L5** Less hand shower system
- SBZ** Seasoned Bronze
- STN** Satin Nickel finish
- MB** Matte Black finish
- BBZ** Brushed Bronze finish

**Note:** Append appropriate -suffix to model number.

### Warranty

**Limited Lifetime** - to the original end purchaser in consumer/residential installations.

**10 Years** - for commercial/industrial installations. Refer to [www.symmons.com/warranty](http://www.symmons.com/warranty) for complete warranty information.



### Model Numbers

- 5505-TRM**  
Shower/Hand Shower Trim, Temptrol Pressure Balancing Shower Valve and Symmons Dual Outlet Diverter valve ordered separately
- 5505TRMTC**  
Shower/Hand Shower Trim with TA-10 flow control spindle and T-12A cap assembly, must order Temptrol valve with Test Cap
- 5505TRM**  
Shower/Hand Shower Trim, Temptrol Pressure Balancing Shower Valve and Symmons Dual Outlet Diverter valve ordered separately

**Note:**

- Append appropriate -suffix to model number.
- When ordering L1-L7 modifiers, remove hyphens from model number.

### Compliance

- ASME A112.18.1/CSA B125.1



## Architectural/ Engineering Specification

Symmons Shower and Hand Shower Trim \_\_\_\_\_ With Elm Shower and Hand Shower Trim, requires Temptrol® pressure balancing shower valve, Requires Symmons Dual Outlet Diverter Valve, metal lever handle, Cradle for hand shower wand, Dual checks for backflow protection, 60" flexible metal hose, 3 mode hand shower wand, 5 mode showerhead, 2.0 gpm (7.6 L/min) flow restrictor, Tub spout not included, components shall be metal and nonmetallic construction, plated in standard Polished Chrome finish, available with TA-10 flow control spindle and T-12A cap assembly for Temptrol valve bodies installed with Test Cap (order p/n 5505TRMTC), For optional in-line vacuum breaker order p/n EF-109. 10 Year commercial Warranty. ASME A112.18.1/CSA B125.1, Complaint. Available options include "-1.5 - 1.5 gpm (5.7 L/min) flow restrictor", "L1 - Less showerhead", "L2 - Less hand shower wand", "L3 - Less showerhead & hand shower wand", "L5 - Less hand shower system", "-SBZ - Seasoned Bronze", "-STN - Satin nickel finish", "-MB - Matte Black finish", "-BBZ - Brushed Bronze finish".

