## Location:



## **SYMMONS** Carrington®

442SH Showerhead **Specification Submittal** 





Model Numbers	Feature Highlights
☐ 442SH Showerhead	<ul><li> 3 inch showerhead</li><li> Three mode, spray jet and pulse</li><li> Polished chrome finish (standard)</li></ul>
Options/ Modifications	Standard flow rate is 2.0 gpm (7.6 L/min)
☐ 1.5 1.5 gpm (5.7 L/min) flow restrictor	
☐ STN Satin Nickel finish	
<b>Note:</b> Append appropriate -suffix to model number.	Warranty
Compliance	Limited Lifetime - to the original end
- ASME A112.18.1/CSA B125.1 - WaterSense 1.5 gpm (5.7 L/min) 2.0 gpm (7.6 L/min)	purchaser in consumer/residential installations.  10 Years - for commercial/industrial installations. Refer to www.symmons.com/warranty for complete warranty information.

## **Architectural/ Engineering Specification**

Symmons Carrington Showerhead \_\_\_\_\_\_ Includes 3 inch showerhead, Three mode, spray jet and pulse, Polished chrome finish (standard), Standard flow rate is 2.0 gpm (7.6 L/min). 10 Year Commercial Warranty. ASME A112.18.1/CSA B125.1, WaterSense 1.5 gpm (5.7 L/min), 2.0 gpm (7.6 L/min) compliant. Available options: "1.5 - 1.5 gpm (5.7 L/min) flow restrictor", "STN - Satin Nickel finish".

## **Dimensions**





Note: Dimensions subject to change without notice.