

5593TRM

Location:

Hand Shower Trim

Specification Submittal

Model Numbers

- ☐ **5593TRM**
Hand Shower Trim

Valve Options:

- 261 Series Temptrol® Shower Valve with TRM modifier
- 161 Series Temptrol Shower Valve requires TC modifier

Feature Highlights

- Elm Hand Shower Trim.
- Requires Temptrol Pressure-Balancing Shower Valve.
- Metal lever handle.
- Dual checks for backflow protection.
- 60" flexible metal hose.
- Single-mode HydroMersion™ hand shower wand with Non-Positive Shutoff (NPSO).
- Standard 2.0 gpm (7.6 L/min) flow restrictor.
- Components shall be metal and nonmetal construction, plated in standard Polished Chrome finish.

Compliance

- ASME® A112.18.1/CSA® B125.1
- WaterSense® 1.5 gpm (5.7 L/min) 2.0 gpm (7.6 L/min)
- Lever handle and hand shower wand meet ADA requirements for operation



Options/Modifications


- ☐ **15** **CG** 1.5 gpm (5.7 L/min) flow restrictor
- ☐ **L2** Less hand shower wand
- ☐ **L7** Less handle
- ☐ **TC** Test Cap Trim (includes TA-10™ & T-12A) *used with 161 Series Temptrol Shower Valve*
- ☐ **BBZ** Brushed Bronze finish
- ☐ **MB** Matte Black finish
- ☐ **STN** Satin Nickel finish

Warranty

Limited Lifetime - for residential installations.

10 Years - for commercial/industrial installations.

Refer to www.symmons.com/warranty for complete warranty information.



SKU Builder


Series	Finish	Modifier	Flow Rate	TRM (required)	TC	Final SKU
5593	STN		15	TRM		5593STN15TRM
5593	MB	L2		TRM	TC	5593MBL2TRMTC

Notes: No more than two modifiers (L1-L7) permitted when ordering. Modifiers will list in numerical order.

Architectural/Engineering Specification

Symmons Elm Hand Shower Trim _____ Includes Elm Hand Shower Trim for Temptrol® Pressure-Balancing Shower Valve. Features metal lever handle, dual checks for backflow protection 60" flexible metal hose, 7-mode HydroMersion hand shower wand with NPSO, and standard 2.0 gpm (7.6 L/min) flow rate. Components shall be metal and nonmetallic construction, plated in standard Polished Chrome finish. 10-Year Commercial Warranty. ASME A112.18.1/CSA B125.1, WaterSense 1.5 gpm (5.7 L/min) and 2.0 gpm (7.6 L/min) compliant. Lever handle and hand shower wand meet ADA requirements for operation. Available options: 15 = 1.5 gpm (5.7 L/min) flow restrictor, L2 = Less hand shower wand, L7 = Less handle, TC = Test Cap Trim, BBZ = Brushed Bronze finish, MB = Matte Black finish, and STN = Satin Nickel finish.

Dimensions



Notes:

- 1) Valve body and piping not included and shown as reference only.
- 2) Plaster shield (p/n T-176) for drywall, plaster, or other type walls 1/2" or greater.
- 3) All dimensions measured from nominal rough-in.
- 4) Dimensions subject to change without notice.